



Mixing water and electricity; finding the energy balance between boilers, chillers, and pumps in hydronic systems.

Jeff Yirak, PE CPMP
LEED AP BD+C, O+M



AIA Quality Assurance



The Building Commissioning Association is a Registered Provider with The American Institute of Architects Continuing Education Systems (AIA/CES). Credit(s) earned on completion of this program will be reported to AIA/CES for AIA members. Certificates of the Completion for both AIA members and non-AIA members are available upon request.

This program is registered with AIA/CES for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product.

Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.



Learning Objectives

1. Describe the energy flows in boilers, chillers, and cooling towers
2. Recognize the opportunity to improve energy performance in hydronic systems
3. Explain the trade-off between boiler, chiller, pump, and cooling tower energy consumption
4. Calculate the energy and dollar cost savings of making adjustments to the system



Why we're here



Pumps

$$V1 \cdot (n2/n1) = V2$$


$$H1 \cdot (n2/n1)^2 = H2$$

$$P1 \cdot (n2/n1)^3 = P2$$


Where V = flow (GPM), H = head (psi),
and P = power (watts)

Pump kWh = pump hp*0.746*hours of operation

Boilers



Boilers



Heat transfer air to water at a coil

$Q = \text{Btu/hr or BTUH}$

$Q = 1.08 * \text{CFM} * \text{delta T for air}$

$Q = 500 * \text{GPM} * \text{delta T for water}$


Assuming a 20 degree delta T for each (45-65 °F air, 180-160 °F water), then each gallon is worth about 463 CFM. If you have a 10,000 CFM AHU, then you're looking at 22 GPM.

$1.08 * 10000 * 20 = 216,000 \text{ BTUH}$


$216000 / (500 * 20) = 21.6 \text{ GPM}$

Coil Performance

LWT and LAT vs GPM at various supply water temperatures



Boilers





Boiler

$\text{MBH} \times \text{Eff}\% \times \$/\text{therm} \times 10 = \text{cost of operation}$

For a 2MMBH boiler operating at 88% efficiency for 2000 hours a year paying \$0.90/therm, the cost of operation would be \$40,000/year. Increasing the efficiency to 92% would cost \$38,298, saving \$1,702 per year.

Achieving an increase of 4% in efficiency would be like going from 135 to 110 degrees entering water temperature.




Cooling Towers

Approach – difference between leaving water temperature and entering wet bulb temperature. In other words, how close can the tower get to the ambient wet bulb temperature.


Range – water delta-t

Temp and flow determined by process


Effect of range on tower size




Effect of approach on tower size



Modulating Cooling Tower Fans



Fan Power versus Wet Bulb Temperature





Chilled Water Systems


Chilled water supply temperature set point

Lift


Condenser water temperature set point and effects on chiller operation

Effect of Condenser Water Temperature

Efficiency with 48 Degree CHWST



Effect of Chilled Water Temperature Set Point





Energy Savings Calculations

Kw

Hp

Time (hours)

Assume \$0.09/kwh

Not considering demand charges

$$\text{COP} = (1 \text{ ton} * 12,000 \text{ btu/ton}) / (0.8 \text{ kW/ton} * 3412 \text{ btu/kw}) = 4.4$$



Condenser Water Pumping

Does increasing the gpm of condenser water to improve chiller COP outweigh the cost of running more pump?

Condenser water system (300 ton chiller)

Pumps

- 2 gpm/ton
- 600 gpm
- $\text{Hp} \times .746 \times \text{hours} = \text{kw}$
- \$1,657
- 6 gpm/ton
- 1800 gpm (30 HP)
- 27 times as much electricity
- \$44,760
- **\$43,103 increase in cost**



Condenser Water System

Chiller

- COP 6.6
 - 0.53 kW/ton
 - 159 kw
 - \$318,000/yr
- COP 7.7
 - 0.45 kW/ton
 - 135 kw
 - \$270,000/yr
 - **\$48,000/yr savings**



Reality

- The system delta T is much lower than design
- Optimize the delta Ts on the coils
 - Coil water flow
- More water is not always better
 - Over/under flow of systems
- The temperature is what matters
- Monitor the results



Jeff Yirak, PE CPMP LEED AP BD+C, O+M
Associate Principal, Commissioning

Wood Harbinger, Inc.
(425) 628-6000
woodharbinger.com

